

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A liquid crystal display device, comprising:

a liquid crystal cell including a liquid crystal layer held between an upper substrate and a lower substrate that oppose each other, and a semi-transparent reflective layer provided on an inner side of the lower substrate, the inner side being adjacent to the liquid crystal layer;

a first elliptically polarizing plate to cause elliptically polarized light to enter the liquid crystal layer through the upper substrate; and

a second elliptically polarizing plate to cause elliptically polarized light to enter the liquid crystal layer through the lower substrate, each of the first elliptically polarizing plate and the second elliptically polarizing plate having a liquid crystal film fixed in ~~hybrid-alignment~~ alignment,

each of the first elliptically polarizing plate and the second elliptically polarizing plate including a polarizer for transmitting linearly polarized light, at least one liquid crystal film fixed in nematic hybrid alignment, and at least one stretched film,

wherein angles formed between phase-retarding axes of the liquid crystal films fixed in nematic hybrid alignment in the first elliptically polarizing plate and the second elliptically polarizing plate and a rubbing axis of the liquid crystal cell are within a range from plus 30 degrees to minus 30 degrees.
- 2-3. (Canceled)
4. (Currently Amended) The liquid crystal display device according to ~~claim 3,~~ claim 1, phase differences in plane of the liquid crystal films fixed in nematic hybrid

alignment in the first elliptically polarizing plate and the second elliptically polarizing plate being within a range from 90 nm to 140 nm.

5. (Canceled)

6. (Currently Amended) A liquid crystal display device, comprising:
a liquid crystal cell including a liquid crystal layer held between an upper
substrate and a lower substrate that oppose each other, and a semi-transparent reflective layer
provided on an inner side of the lower substrate, the inner side being adjacent to the liquid
crystal layer;

a first elliptically polarizing plate to cause elliptically polarized light to enter
the liquid crystal layer through the upper substrate; and

a second elliptically polarizing plate to cause elliptically polarized light to
enter the liquid crystal layer through the lower substrate, each of the first elliptically
polarizing plate and the second elliptically polarizing plate having a liquid crystal film fixed
in hybrid alignment,

each of the first elliptically polarizing plate and the second elliptically
polarizing plate including the polarizing plate, at least one liquid crystal film fixed in discotic
hybrid alignment, and at least one stretched film, The liquid crystal display device according
to claim 5,

wherein angles formed between phase-advancing axes of the liquid crystal
films fixed in discotic hybrid alignment in the first elliptically polarizing plate and the second
elliptically polarizing plate and ~~an axis including the distinct viewing direction~~ a rubbing axis
of the liquid crystal layer, ~~being cell are~~ within a range from plus 30 degrees to minus 30
degrees.

7-12. (Canceled)

13. (Original) The liquid crystal display device according to claim 4, the liquid crystal cell having a layer-thickness adjusting layer that makes the thickness of the liquid crystal layer smaller in a reflective display region than in a transmissive display region.

14. (Original) The liquid crystal display device according to claim 13, the liquid crystal layer adopting a twisted nematic mode.

15. (Original) The liquid crystal display device according to claim 13, the liquid crystal layer adopting parallel alignment, and the twist angle therein being zero degrees.

16. (Original) An electronic apparatus, comprising the liquid crystal display device according to claim 1.